



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

E05D 13/00, E05F 1/08

(11) International Publication Number:

WO 90/15216

(43) International Publication Date:

13 December 1990 (13.12.90)

(21) International Application Number:

PCT/SE90/00364

A1

(22) International Filing Date:

30 May 1990 (30.05.90)

(30) Priority data:

8901932-7

30 May 1989 (30.05.89)

SE

(71) Applicant (for all designated States except US): CRAW-FORD DOOR AB [SE/SE]; Box 160, S-423 21 Torslanda (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BENGTSSON, Fred [SE/ SE]; Kyrkås Trappor 3, S-433 31 Partille (SE).


(74) Agent: AWAPATENT AB; Box 53252, S-400 16 Göteborg (SE).

(81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI tent), MW, NL, NL (European patent), NO, RO, SD, SE, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent), US.

Published

With international search report. With amended claims.

(54) Title: A SPRING ATTACHMENT MEMBER



(57) Abstract

A spring attachment member (1) for securement of a door balancing spring (2) which is coiled about a shaft (3). In accordance with the invention at least one (2A) of the ends of the spring (2) is arranged to be secured to a two-piece attachment (1) enclosing the spring mounting shaft (3). One attachment member part (11) is slidable in the lengthwise direction (6-7) as well as being arranged to turn (8-9) about said shaft (3). The second, complementary attachment member part (12) is arranged for sliding movement in the lengthwise direction (6-7) of the shaft (3) but is non-rotationally mounted thereon. The two attachment member parts (11, 12) are arranged to be securely interconnected.

DESIGNATIONS OF "DE"

Until further notice, any designation of "DE" in any international application whose international filing date is prior to October 3, 1990, shall have effect in the territory of the Federal Republic of Germany with the exception of the territory of the former German Democratic Republic.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AТ	Austria	ES	Spain	MC	Monaco
ΑU	Australia	FI	Finland	MG	Madagascar
BB	Barbados	FR	France	ML	Mali
BE	Belgium	GA	Gabon	MR	Mauritania
8F	Burkina Fasso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GR	Greece	NL	Netherlands
BJ	Benin	HU	Hungary	NO	Norway
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	SD	Sudan
CF	Central African Republic	KP	Democratic People's Republic	SE	Sweden
CC	Congo		of Korea	SN	Senegal
CH	Switzerland	KR	Republic of Korea	รบ	Soviet Union
CM	Cameroon	LI	Liechtenstein	TD	Chad
DE	Germany, Federal Republic of	LK	Sri Lanka	TC	Togo
DK	Denmark	LU	Luxembourg	US	United States of Ame

A SPRING ATTACHMENT MEMBER

The present invention concerns a spring attachment member for securement of a door balancing spring which is coiled about a shaft.

The main purpose of the present invention is prima
7 rily to provide a spring attachment member which is arranged in such a manner as to allow the door balancing torsional spring/springs to be tensioned upon downwards movements (closing) of the door.

This purpose is achieved in accordance with the
invention with the aid of a spring attachment member
which is characterized in that at least one of the ends
of the spring is arranged to be secured to a split twopiece spring attachment member enclosing the spring
shaft, one attachment member part being slidable in
the lengthwise direction of the shaft as well as being
arranged to turn about said shaft, and in that the second,
complementary attachment member part is arranged for
sliding movement in the lengthwise direction of the
shaft but is non-rotationally mounted thereon, said
two attachment member parts arranged to be securely
interconnected.

One preferred embodiment of the invention will be described in closer detail in the following with reference to the accompanying drawings, wherein

25 Fig. 1 shows a spring attachment member and the associated spring in a disconnected, pre-assembly position.

Fig. 2 illustrates the spring attachment member in the tightened assembly position, and

Fig. 3 illustrates the attachment member in its fully mounted position, the alternative displaced position of the attachment member being shown in broken lines.

The subject invention concerns a spring attachment

member 1 for a door balancing spring 2 which is coiled about its associated door spring shaft 3, one end 3A of said spring being non-rotationally secured to a cable drum 4 on which drum 4 is wound a cable 5 which is attached to a door. The door is guided for movement along tracks extending alongside the opening to be closed by the door.

In accordance with the teachings of the invention one end 2A of the spring 2 which preferably is of the helically wound type, is arranged to be attached to a split, two-piece spring attachment member 1 which encloses the spring shaft 3. One attachment member part 1 of the attachment member 1, which part is intended to be attached to the spring 2 and to be positioned next to said spring, is mounted on the shaft 3 in such a manner as to be displaceable along said shaft 3 in the directions indicated by arrows 6, 7. In addition, this attachment member part 1 is mounted for rotational movement about the shaft 3 in the direction indicated by arrows 8-9.

The second complementary attachment part 1² of the two-piece attachment member 1 is mounted on the shaft 3 for movement in the longitudinal directions thereof indicated by arrows 6-7. However, this second attachment member part 1² is non-rotationally attached to the shaft 3 and consequently these two components turn together as one single unit.

In accordance with the teachings of the invention the two attachment member parts are interconnectable, for example by means of non-threaded through-holes 10 formed in e.g. the second attachment member part 1² and threaded holes 11 formed in the other attachment member part 1¹, and by means of threaded attachment bolts 12 arranged to be received in the respective holes 10, 11 so as to form an integrated spring attachment member 1 which is non-rotationally secured to the spring shaft 3 but displaceable in the longitudinal directions

10

15

20

25

30

6-7 of the shaft 3.

Preferably, the two attachment member parts 1, 1² are disc-shaped, presenting e.g. a circular circumferential configuration, with the first attachment member part 1 having a circular central opening to allow free rotational movement of said attachment part in coupling position I around the spring shaft 3 whereas the second attachment member part 12 has a central opening 13 of irregular configuration in order to be turned together with and by said spring shaft 3. Preferably, . the central opening 13 of said second attachment member part 12 has a circumferential configuration which essentially matches the shape of the spring shaft 3. The spring shaft 3 may for instance have a non-round configuration or a polygonal circumferential configuration, such as a hexagonal shape, in which case the central opening 13 has a configuration matching that of the spring shaft 3, i.e. the central opening 13 has a congruent hexagonal configuration.

The hub portion 14 of the first attachment member part 1¹ is arranged to receive a bearing means of complementary configuration projecting in axial direction from the second attachment member part 1².

The second end 2B of the spring 2 may be attached to a similar attachment member to that described in the aforegoing or to a conventional attachment member 15, for instance of the kind illustrated in the drawing figures and comprising a disc-shaped attachment member part 16 to which the spring 2 is secured by means of a screw 17 and which attachment part 16 is arranged for securement in a wall-mounted bracket 18 which by means of screws 19 is fastened to the intended mounting place.

Attachment member part 1 of the intended two-piece spring attachment member 1 is formed with reception means 21 designed in conformity with a manually actuable turning element 20. The reception means may be e.g.

25

---a-number of apertures 2-1-adapted to receive one end 20A of a lever 20. Preferably, a plurality of lever receiving apertures 21 are distributed along the circumference of the associated attachment member part 1'.

Finally, the spring 2 is secured to the attachment member part 1 by means of a bolt joint 22.

How the spring attachment member in accordance with the invention functions should be apparent from the aforegoing and from a study of the drawings. Briefly, 10 the entire spring unit 23 is lifted as one single piece to the intended position of use to be secured in that? position by means of screws. At this stage the spring 2 is in its untensioned, unloaded coupling position I, in which its one spring end 2A is attached to the attachment member part 11. By means of the lever 20 said attachment member part 1 is turned in the rotational direction 9 to tension the spring 2 in such a manner that the latter obtains the correct desired spring tension, whereupon the attachment member part 1 and the second attachment part 1² are jointed together by means of screws, said second attachment member part being rotated together with the spring mounting shaft 3 which is interconnected with the wire drum 4. Consequently, the spring 2 need not be tightened before the door hoisting cable 5 is secured to the door in its intended position.

In the interconnected position II of the attachment member 1 the latter is freely displaceable in the horizontal directions 6-7 in dependence on the amount of extension and contraction, respectively, of the spring 2 in the various setting positions thereof.

The invention is not limited to the embodiments described in the aforegoing and illustrated in the drawings but various modifications are possible within the scope of the appended claims.

CLAIMS

- 1. A spring attachment member (1) for securing a door balancing spring (2) which is coiled about a shaft (3), c h a r a c t e r i z e d in that at least one (2A) of the ends of the spring (2) is arranged to be secured to a split, two-piece spring attachment member (1) enclosing the spring shaft (3), one attachment member part (1) being slidable in the lengthwise direction (6-7) of the shaft as well as being arranged to turn (8-9) about said shaft (3), and in that the second, complementary attachment member part (1²) is arranged for sliding movement in the lengthwise direction (6-7) of the shaft (3) but is non-rotationally mounted thereon, said two attachment member parts (1¹, 1²) arranged to be securely interconnected.
- 2. A spring attachment member as claimed in claim 1, c h a r a c t e r i z e d in that the attachment member parts (1¹, 1²) are disc-shaped, one (1¹) of said attachment member parts having a circular hub opening whereas the second attachment member part (1²) is formed with a central opening (13) of irregular configuration.
 - 3. A spring attachment member as claimed in claim 2, wherein said spring shaft (3) has a polygonal peripheral configuration, e.g. a hexagonal configuration, c h a r a c t e r i z e d in that the central opening (13) of said second attachment member part (1²) has a peripheral configuration matching that of the spring shaft (3).
 - 4. A spring attachment member as claimed in any one of the preceding claims, c h a r a c t e r i z e d therein that the central portion (14) of said first attachment member part (1¹) is arranged to be fitted onto a bearing means of complementary configuration projecting in the axial direction (7) from said second attachment member part (1²).

- 5. A spring attachment member as claimed in any one of the preceding claims, c h a r a c t e r i z e d therein that the two attachment member parts (1¹, 1²) are formed respectively with a through-hole (10) and with a threaded hole (11) for reception in said holes of attachment bolts (12) serving to join the two attachment member parts (1¹, 1²) together for the purpose of forming an attachment member (1) which is non-rotationally secured to the spring shaft (3) but may be displaced in the longitudinal direction (6, 7) of said shaft.
- 6. A spring attachment member as claimed in any one of the preceding claims, c h a r a c t e r i z e d therein that the first attachment member part (1¹) is formed with reception means (21) designed in conformity with a manually actuable turning element (20), said reception means (21) being e.g. a number of apertures (21) adapted for reception therein of a lever (20).
- 7. A spring attachment member as claimed in claim 6,
 20 c h a r a c t e r i z e d in that a plurality of lever
 reception apertures (21) are distributed along the circumference of the first attachment member part (11).
- 8. A spring attachment member as claimed in any one of the preceding claims, c h a r a c t e r i z e d
 25 therein that a bolt joint (22) secures the spring (2) to the first attachment member part (1¹).

AMENDED CLAIMS

[received by the International Bureau on 19 October 1990 (19.10.90); original claim 1 amended; other claims unchanged (2 pages)]


- 1. A spring attachment member (1) for securing a door balancing spring (2) of the helically wound type through which passes a shaft (3), said spring attachment member arranged to non-rotationally secure one spring end to said shaft, characterized in that it comprises two releasably interconnected parts, one part (1¹) of which is rotational relative to the shaft but non-rotational relative to said spring end whereas the second part (12) which is interconnectable with the first part, is non-rotationally but at the 10 same time slidably mounted on the shaft (3) in such a manner that the end attachment (1), in its assembled condition, is free to move axially, also under conditions of spring (2) activity, while being guided by said shaft, 15 whereas the attachment member part attached to the spring, when disconnected from the other part, may be turned relative to the shaft and bring along said spring end in its turning movement until attainment of the desired spring tension relative to said shaft, whereupon it is locked in that position by mutual interconnection 20 of that two spring attachment member parts.
 - 2. A spring attachment member as claimed in claim 1, c h a r a c t e r i z e d in that the attachment member parts $(1^1, 1^2)$ are disc-shaped, one (1^1) of said attachment member parts having a circular hub opening whereas the second attachment member part (1^2) is formed with a central opening (13) of irregular configuration.
- 3. A spring attachment member as claimed in claim 2, wherein said spring shaft (3) has a polygonal peripheral configuration, e.g. a hexagonal configuration, c h a r a c t e r i z e d in that the central opening (13) of said second attachment member part (1²) has a peripheral configuration matching that of the spring shaft (3).

25

10


15

- 4. A spring attachment member as claimed in any one of the preceding claims, characterized therein that the central portion (14) of said first attachment member part (1¹) is arranged to be fitted onto a bearing means of complementary configuration projecting in the axial direction (7) from said second attachment member part (1²).
- 5. A spring attachment member as claimed in any one of the preceding claims, c h a r a c t e r i z e d therein that the two attachment member parts (1¹, 1²) are formed respectively with a through-hole (10) and with a threaded hole (11) for reception in said holes of attachment bolts (12) serving to join the two attachment member parts (1¹, 1²) together for the purpose of forming an attachment member (1) which is non-rotationally secured to the spring shaft (3) but may be displaced in the longitudinal direction (6, 7) of said shaft.
- 6. A spring attachment member as claimed in any one of the preceding claims, characterized therein that the first attachment member part (1¹) is formed with reception means (21) designed in conformity with a manually actuable turning element (20), said reception means (21) being e.g. a number of apertures (21) adapted for reception therein of a lever (20).
 - 7. A spring attachment member as claimed in claim 6, c h a r a c t e r i z e d in that a plurality of lever reception apertures (21) are distributed along the circumference of the first attachment member part (1¹).
- 8. A spring attachment member as claimed in any one of the preceding claims, characterized therein that a bolt joint (22) secures the spring (2) to the first attachment member part (1¹).




SUBSTITUTE SHEET

DEST AVAILABLE COPY



SUBSTITUTE SHEET ___ AVAILABLE COPY





International Application No PCT/SE 90/00364

				,		
		F SUBJECT MATTER (if several classif				
IPC5:	g to Internation E 05 D 13	al Patent Classification (IPC) or to both N 8/00, E 05 F 1/08	lational Classification and IPC			
II EIEI D	S SEARCHED					
II. FIELD	3 SEARCHED	Minimum Docume	ntation Searched 7			
Classificati	ion System		Classification Symbols			
•						
IPC5	E	05 D; E 05 F				
	· · · · · · · · · · · · · · · · · · ·	Documentation Searched other	r than Minimum Documentation	<u> </u>		
		to the Extent that such Document	s are included in Fields Searched ⁸			
SE,DK,	FI,NO cla	sses as above				
		SIDERED TO BE RELEVANT®				
Category *	1	of Document, ¹¹ with indication, where ap		Data		
				Relevant to Claim No.13		
X	15 A	.922370 (C.G. JOHNSON ET August 1933.	ALJ	1,5-8		
		the whole document				
Y				2-5		
		-				
v	CF C .	06106 (F. A. FODG. FT. 41)				
Υ		86196 (E A FORS ET AL) the whole document	12 November 1963,	2-5		
	266	the whole document		-		
Υ		8635277 (BAHNSEN) 18 Jan	uary 1972,	2-5		
	see	the whole document				
	·	· —-				
Υ	IIS A 2	2097242 (D.M. ROBINSON)	26 October 1927	2-5		
'	see	the whole document	20 October 1937,	2-5		
				j		
	1					
* Speci	al categories	of cited documents; 10		Ab - 1-4		
		g the general state of the art which is not particular relevance	"I" later document published after or priority date and not in cont cited to understand the princip	lict with the application but le or theory underlying the		
"E" ear	rlier document	but published on or after the international	1			
1	ng date	Pay them doubte on priority claim(s) or	"X" document of particular relevan cannot be considered novel or involve an inventive step	cannot be considered to		
which is cited to establish the publication date of another citation or other special reason (as specified) "Y" document of particular relevance, the claimed invention						
"O" document referring to an oral disclosure, use, exhibition or						
	igi- ingalia		in the art.	•		
	er than the pric	ed prior to the international filing date bu prity date claimed	"&" document member of the same	patent family		
		etion of the International Search	Date of Mailing of this International	Search Report		
OLD A	ugust 199	70	1990 -08- 24			
Internation	nal Searching A	uthority	Signature of Kuthorized Officer	/		
	SWEDIS	SH PATENT OFFICE	Christer Wendenius	sunc		
1		· · · · · · · · · · · · · · · · · · ·				

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.PCT/SE 90/00364

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on

10-06-27

The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report		Publication date	Patent family member(s)	Publication date	
US-A-	1922370	33-08-15	NONE		
SE	186196	63-11-12	NONE		
US-A-	3635277	72-01-18	NONE		
US-A-	2097242	37-10-26	NONE		

00010 - WO 9015216A1 | >



Internation Destion No PCT/EP 03/03132

A. CLASSIF	ICATION OF SUBJECT MATTER £05D13/00			
According to	International Patent Classification (IPC) or to both national classification	lon and IPC		
B. FIELDS S	SEARCHED			
Minimum doo	cumentation searched (classification system tollowed by classification E 05D	n symbols)		
Documentati	on searched other than minimum documentation to the extent that su	ch documents are included in the fields se	arched	
Electronic de	ata base consulted during the International search (name of data base	e and, where practical, search terms used)		
EPO-In	ternal			
	•			
	ENTS CONSIDERED TO BE RELEVANT	went nessages	Relevant to dalm No.	
Category °	Citation of document, with indication, where appropriate, of the rele			
Х	US 1 922 370 A (BLODGETT HERBERT 15 August 1933 (1933-08-15)	C ET AL)	1-3,8-10	
Α	page 1, line 100 -page 2, line 32	; figures	4-7	
			1 2 9 10	
Х	US 2 116 329 A (STURMAN ROBERT E) 3 May 1938 (1938-05-03)	1-3,8-10		
	column 2, line 12 - line 48; figu	res 1-3		
x	WO 90 15216 A (CRAWFORD DOOR AB)		1-3,8-10	
"	1 13 December 1990 (1990-12-13)	figures		
	page 2, line 8 -page 4, line 30;	i igui co		
	·			
Fur	ther documents are listed in the continuation of box C.	X Patent family members are listed	d in annex.	
	ategories of cited documents :	"T" later document published after the into or priority date and not in conflict with	n ina applicator pui	
'A' document defining the general state of the art which is not considered to be of particular relevance invention				
"E" earlier document but published on or after the international "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance; the claimed inventiging date "X" document of particular relevance;				
"L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another "Y' document of particular relevance; the claimed invention stan when the				
O docur	on or other special reason (as specified) nent referring to an oral disclosure, use, exhibition or r means	document is combined with one or a ments, such combination being obvi		
other means *P* document published prior to the international filing date but later than the priority date claimed **E** document member of the same patent family				
1	e actual completion of the international search	Date of mailing of the international s	earch report	
*	10 June 2003	20/06/2003		
Name and	d mailing address of the ISA	Authorized officer		
	European Patent Office, P.B. 5818 Patentlaan 2 NL – 2280 HV Rijswijk Tel. (+31–70) 340–2040, Tx. 31 651 epo ni,	Di Renzo, R		
1	Fax: (+31-70) 340-2016	DI Kelizo, K		



Internation Cation No
PCT/EP 03/03132.

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 1922370	Α	15-08-1933	NONE		
US 2116329	A	03-05-1938	NONE		<u> </u>
WO 9015216	Α	13-12-1990	SE AU SE WO	464821 B 5825090 A 8901932 A 9015216 A1	17-06-1991 07-01-1991 01-12-1990 13-12-1990